

IKA

designed for scientists



MATRIX Orbital Delta F1.5

/// Технический паспорт

The IKA Matrix Orbital Δ F1.5 is part of a new and powerful product family of thermoshakers available. IKA Matrix Orbital Δ F1.5 mixes and heats with a fixed insert for 24 x 1,5 ml tubes. Whether its blood samples, pharmaceutical agents, DNA/RNA samples or ELISA assays – samples with even the smallest volumes mix reliably and completely in all laboratory applications. No cross-contamination and an optimal mixing result.

In addition, IKA Matrix Orbital Δ F1.5 comes with numerous user-friendly features:

- Large and clear display with a convenient menu structure allows for intuitive operation

www.ika.com

Производитель оставляет за собой право технических изменений



IKAworlwide



IKAworlwide /// #lookattheblue



@IKAworlwide



designed for scientists

- Speeds of up to 1,500 rpm and shaker diameter of 3 mm ensure the liquid mixes quickly and effectively
- Two different speed modes for gentle heating of the samples
- Programmable ramps allow for automatic execution of mixing and heating tasks
- Smart speed adjustment according to insert, attachment and filling volume
- Aluminum die cast housing ensures secure positioning, excellent stability and everyday robustness



designed for scientists

Технические данные

Траектория встряхивания	Орбитальная
Диаметр орбиты [mm]	3
Maximum load [kg]	0.3
Разрешенное время во вкл. состоянии [%]	100
Скорость мин.(регулируемая) [rpm]	300
Диапазон вращающего момента [rpm]	0 - 1500
Индикатор скорости	TFT
Отклонение скорости [\pm rpm]	30
Контроль диапазона скоростей	10 RPM Steps
Таймер	да
Дисплей таймера	TFT
Контроль времени мин. [s]	1
Контроль времени макс. [min]	6000
Режим работы	timer, continuous and program operation
Диапазон нагревания температур [$^{\circ}$ C]	Температура окр. среды $+4^{\circ}$ - 100
Мощность нагрева [W]	100
Контроль нагрева	TFT
Колебание температур нагрева [\pm $^{\circ}$ C]	1
Temperature control accuracy [\pm $^{\circ}$ C]	0.5
Temperature stability [$^{\circ}$ C]	0.5
Temperature homogeneity [\pm $^{\circ}$ C]	0.5 (@ 20 $^{\circ}$ C ... 45 $^{\circ}$ C); 1.5
Heating rate [$^{\circ}$ C/min]	11
Индикатор температуры	да
Number of reaction vessels	24x 1.5 ml
Размеры [mm]	216 x 158 x 351
Вес [kg]	9.2
Допустимая температура окружающей среды [$^{\circ}$ C]	5 - 40
Допустимая относительная влажность [%]	80
Класс защиты согласно DIN EN 60529	IP 21
Разъем RS 232	да
Разъем USB	да
Напряжение [V]	100 - 240
Частота [Hz]	50/60
Потребляемая мощность [W]	240
Power input max. [W]	240
Fuse	2x T4A 250V