

IKA

designed for scientists



RV 3 with Dry Ice Condenser, coated

/// Технический паспорт

The RV 3 Rotary Evaporator is the manual basic model in the family of IKA Rotation Evaporators. It finds a multitude of uses in the chemical, pharmaceutical, and biotechnology industries, in research and development, in manufacturing and quality assurance, in laboratories, and in plant construction. Digital displays for speed and heating bath temperature enable optimum control of all distillation processes.

New: 4 liter heating bath
integrated safety lift-out function in case of power failure
water heating bath with carrying handles

www.ika.com

Производитель оставляет за собой право технических изменений



IKAworlwide



IKAworlwide /// #lookattheblue



@IKAworlwide



designed for scientists

locking button for fixing heating bath temperature
locking mechanism: red indicator shows unlocked position of the vapor tube
flask clamping mechanism with integrated push-off function for easy exchange of evaporation flasks
manual lift for precise positioning of the glassware
adjustable immersion angle
single-handed manual lift handling, suitable for left and right-handed operators
speed range: 5 - 300 min⁻¹
low device voltage (24V) ensures user safety
compatible with the entire range of IKA RV 10 glassware

Package description: With heating bath HB eco and RV 10.40 dry ice condenser coated glassware set



designed for scientists

Технические данные

Тип конденсатора	вертикальный
Охлаждающая поверхность [см ²]	1500
Тип привода	Постоянный ток
Диапазон вращающего момента [rpm]	20 - 300
Допустимое отклонение скорости при заданной скорости вращения < 100 об./мин [±rpm]	1
Допустимое отклонение скорости при заданной скорости вращения > 100 об./мин [±%]	1
Подъем	вручную
Подъем [mm]	150
Диапазон нагревания температур [°C]	Температура окр. среды - 99
Размеры [mm]	440 x 530 x 330
Вес [kg]	28.3
Допустимая температура окружающей среды [°C]	5 - 40
Допустимая относительная влажность [%]	80
Класс защиты согласно DIN EN 60529	IP 20
Напряжение [V]	100 - 240
Частота [Hz]	50/60
Потребляемая мощность [W]	1400